

AquaTec, Inc. 1235 Shappert Drive Rockford, Illinois 61115 USA

DESIGN CRITERIA FORM

Telephone: (815) 654-1500 FAX: (815) 654-0038

mg/l

CI

WebSite: http://www.aquatecinc.com/

For a preliminary proposal please complete as much of this form as possible and submit by fax or mail to AquaTec, Inc.

Company:					Contact::			
Address:					City:			
State/Province:			Zip:		Country:			
Telephone:_					_ FAX:_	·		
Operation:hours/day _				City: Zip: Country: FAX:days/week days/year				
Retrofit:		d	ays allow	ved De	esired Co	mpletion:		
Industrial: P	Produc	ction						
		INFLU	ENT I	EFFLUE	NT (Permit) <u>Comments</u>		
		Average	Maximum	Average	Maximum			
Flow	mgd							
Water Temp	°C							
Ambient Temp	°C							
BOD5	mg/l							
COD	mg/l							
рН	units							
TSS	mg/l							
VSS	mg/l							
NH3-N	mg/l							
TKN	mg/l							
Ortho P	mg/l							
CaCO3	mg/l							
SO4	mg/l							
FOG	mg/l							
Na	mg/l							

Influent Screen Needed: □ No □ Yes, Type Grit removal: □ No □ Yes Storm Provisions:
Effluent Discharge
Type: □ Stream/River □ Lake □ Reservoir □ SubSurface Drip □ Direct Land Spray □ Other
Disinfection: □ UV □ Chlorine □ Ozone □ None □ Other Dewatering Desired: □ No □ Yes, Type Desired
Tankage
Existing: Size:HighWidthLengthDiameter Type: □ Concrete □ Fiberglass □ Glass Lined Steel □ Coated Steel □ Lagoon Drawings: Please include with Submittal Equalization: Capacity gal Size:
New application: Available Space: Submit drawing/sketch if possible Type of Tank Desired: □ Concrete □ Fiberglass □ Glass Lined Steel □ Coated Steel Elevation: □ Above Ground □ Partial □ Below Ground
System Preference □ Sequenced Batch Reactor □ Anaerobic □ Lagoon □ Oxidation Ditch □ Membrane □ "Packaged Plant" □ Other
Miscellaneous Power: 230 460 volt 30 60 hertz 50 hertz Other Power Cost: cents per Kilowatt GAS cost: per Therm Sewer Surcharge BOD, cost per pound Sludge Disposal Costs per gallon & gallons per day Pumping Needed Influent Effluent Other Site Elevation: feet A.M.S.L.
Other: